

T Pro

## Buckle Mask Type

Outdoor Led Rental Transparent Screen



DIGITAL MEDIA

Port Number	T Pro-F3.9	TPro-F7.8	TPro-F10.4
Pixel Pitch	3.9683*7.8125mm	7.8125mm	10.4167mm
LED Configuration	SMD1921	SMD1921	SMD1921
Brightness	4000-4500CD/m <sup>2</sup>	4000-4500CD/m <sup>2</sup>	4000-4500CD/m <sup>2</sup>
Pixel Density	32256dot/m <sup>2</sup>	16384dot/m <sup>2</sup>	9216dot/m <sup>2</sup>
Transparency	≥65%	≥70%	≥80%
Cabinet Size	1000×500×76mm	1000×500×76mm	1000×500×76mm
Cabinet Resolution	252×64dot	128×64dot	96×48dot
Cabinet Weight	6.5kg	6.5kg	6.5kg
IP Rating	IP54	IP54	IP54
Environment	Outdoor	Outdoor	Outdoor
View Angle(V/H)	140° /140°	140° /140°	140° /140°
View Distance	4m	8m	10m
Grey Scale	16bit	16bit	16bit
Max Consumption	600W/m <sup>2</sup>	600W/m <sup>2</sup>	600W/m <sup>2</sup>
Ave Consumption	220W/m <sup>2</sup>	220W/m <sup>2</sup>	220W/m <sup>2</sup>
Refresh Rate	3840Hz	3840Hz	3840Hz
Input Voltage	AC110~ 240V, 50/60Hz		
Control Mode	Synchronous display with control PC By DVI/Aynchronous		
Input Signal	Composite,S-Vido,Component,VGA,DVI,HDMI,HD_SDI		
Temperature (work/store)	0° C~40° C(work) , -20° C~60° C(store)		
Humidity (work/store)	35%~85%(work),10%~90%(store)		
Operating Life	≥100,000hours		
Cabinet Material	Die-casting Aluminium		
Installation Methord	Hanging/Stacking		
Package	Flightcase		